

High Reliability 0.56-inch Triple-Digits 7-Segment Numeric Displays

**SND-630(A)
SND-637(A)**

GENERAL DESCRIPTION

The SND-630 and SND-637 series are high degree of reliability epoxy resin molded three-digit 7-segment LED displays of which character height is 0.56-inch (14.1mm) and available in red, orange and yellow-green emitting colors. The standard units are constructed with black face and milky white segment color.


FEATURES

1. High brightness and high contrast
2. Low power consumption; Directly drive with I.C
3. Wide angle viewing
4. Solid state reliability; Long operation life
5. Match to SND640/647 series for 7 digits of applications
6. Cathode-common (SND630) and anode-common (SND637) types available

Actual size





PACKAGE DIMENSIONS
SCALE 1:1 (mm)




PIN ARRANGEMENT

(Top View)



SND637/SND-637 A Anode-common

All diodes are reversed polarity



SND630 A Cathode-common



SAM KWANG SEMICONDUCTOR CO., LTD.

803 Silla Techno Vil., 39-3 Dang-dong Kunpo-City Kyungki-do, Korea, TEL:031-456-1444/1484, FAX:031-456-4224 <http://www.samkwangled.com>

Red SND 630/637R (GaP)

Absolute Maximum Ratings ($T_a = 25^\circ C$)

Power dissipation/Total	960	mW
Power dissipation/Seg	40	mW
Forward current	20	mA
Peak forward current	60*	mA
Reverse voltage	4	V
Operating temperature	-25 ~ +85	°C
Storage temperature	-55 ~ +100	°C

Electrical/Optical Characteristics ($T_a = 25^\circ C$)

Parameter	Symbol	Conditions	Min	Typ	Max.	Unit
Forward voltage/Seg	V_F	$I_F = 10\text{mA}$	—	2.1	2.3	V
Reverse current/Seg	I_R	$V_R = 4\text{V}$	—	—	10	μA
Luminous intensity/digit	I_V	$I_F = 10\text{mA}$	200	700	—	μcd
Peak wavelength	λ_P	$I_F = 10\text{mA}$	—	700	—	nm
Spectral line halfwidth	$\Delta\lambda$	$I_F = 10\text{mA}$	—	30	—	nm

Orange SND 630/637SR (GaAsP/GaP)

Absolute Maximum Ratings ($T_a = 25^\circ C$)

Power dissipation/Total	960	mW
Power dissipation/Seg	40	mW
Forward current	20	mA
Peak forward current	60*	mA
Reverse voltage	4	V
Operating temperature	-25 ~ +85	°C
Storage temperature	-55 ~ +100	°C

Electrical/Optical Characteristics ($T_a = 25^\circ C$)

Parameter	Symbol	Conditions	Min	Typ	Max.	Unit
Forward voltage/Seg	V_F	$I_F = 10\text{mA}$	—	2.0	2.2	V
Reverse current/Seg	I_R	$V_R = 4\text{V}$	—	—	10	μA
Luminous intensity/digit	I_V	$I_F = 10\text{mA}$	600	1300	—	μcd
Peak wavelength	λ_P	$I_F = 10\text{mA}$	—	635	—	nm
Spectral line halfwidth	$\Delta\lambda$	$I_F = 10\text{mA}$	—	35	—	nm

Yellow-green SND 630/637UG (GaP)

Absolute Maximum Ratings ($T_a = 25^\circ C$)

Power dissipation/Total	960	mW
Power dissipation/Seg	40	mW
Forward current	20	mA
Peak forward current	60*	mA
Reverse voltage	4	V
Operating temperature	-25 ~ +85	°C
Storage temperature	-55 ~ +100	°C

Electrical/Optical Characteristics ($T_a = 25^\circ C$)

Parameter	Symbol	Conditions	Min	Typ	Max.	Unit
Forward voltage/Seg	V_F	$I_F = 10\text{mA}$	—	2.1	2.3	V
Reverse current/Seg	I_R	$V_R = 4\text{V}$	—	—	10	μA
Luminous intensity/digit	I_V	$I_F = 10\text{mA}$	600	1300	—	μcd
Peak wavelength	λ_P	$I_F = 10\text{mA}$	—	565	—	nm
Spectral line halfwidth	$\Delta\lambda$	$I_F = 10\text{mA}$	—	30	—	nm

Red SND 630/637UR (GaAlAs)

Absolute Maximum Ratings ($T_a = 25^\circ C$)

Power dissipation/Total	960	mW
Power dissipation/Seg	40	mW
Forward current	20	mA
Peak forward current	60*	mA
Reverse voltage	4	V
Operating temperature	-25 ~ +85	°C
Storage temperature	-55 ~ +100	°C

Electrical/Optical Characteristics ($T_a = 25^\circ C$)

Parameter	Symbol	Conditions	Min	Typ	Max.	Unit
Forward voltage/Seg	V_F	$I_F = 10\text{mA}$	—	1.85	2.1	V
Reverse current/Seg	I_R	$V_R = 4\text{V}$	—	—	10	μA
Luminous intensity/digit	I_V	$I_F = 10\text{mA}$	1800	3000	—	μcd
Peak wavelength	λ_P	$I_F = 10\text{mA}$	—	660	—	nm
Spectral line halfwidth	$\Delta\lambda$	$I_F = 10\text{mA}$	—	20	—	nm

* Pulse Width 1 ms

Duty Cycle 1/5